




Window Air Conditioner

USER MANUAL

8000Btu, 12000Btu



Thank you for purchasing this Window Air Conditioner. Before operating this unit, please read these instructions completely and keep the manual ready for further reference. Si desea, puede obtener este manual en español en www.classic-america.com.

CONTENTS

■ Important Safety Instructions	01
■ Electrical Requirements	03
■ Packing List	05
■ Installation & Assembly Instructions	06
■ Using Your Air Conditioner	13
■ Care and Cleaning	18
■ Troubleshooting	20

Important Safety Instructions

Before installing and using your air conditioner, please read this owner's manual carefully. Store this manual in a safe place for future reference. Your safety and the safety of others is very important to us. Please pay attention to all safety messages outlined in this user manual.



Warning

To reduce the risk of fire, electrical shock or injury when using your air conditioner, follow the basic precautions below:

- Plug into a grounded 3 prong outlet.
- Do not remove the ground prong.
- Do not use a plug adapter.
- Do not use an extension cord.
- Unplug the air conditioner before servicing.
- Use two or more people to move and install the air conditioner.



This is a safety alert symbol. This symbol alerts you to potential hazards that can harm you or others or even cause death. All safety messages will directly follow the safety alert symbol and/or the words "DANGER" or "WARNING".



Danger

Failure to immediately follow these instructions may cause serious injury or even death.



Warning

All Safety messages alert you of potential hazards, how to reduce the chance of injury, and what can happen if instructions are not followed correctly.

Introduction to Refrigerants R32

The refrigerants used for these air conditioners are environmentally friendly hydrocarbons R32. This kind of refrigerant is combustible and odorless. It can burn and explode under certain condition. However, there will be no risk of burning and explosion if you comply with these instructions to install your air conditioner in a room with an appropriate area and use it correctly.

Compared with ordinary refrigerants, Refrigerant R32 is environmentally friendly and does not destroy the ozone sphere and its value of greenhouse effect is also very low.



Warning

- Please read the manual before installation, use or maintenance.
- Do not use means to accelerate the defrosting process or to clean, other than those recommended by the manufacturer.
- Do not pierce or burn the appliance.
- The appliance shall be stored in a room without continuously operating heat (for example: open flames, an operating ignition gas appliance or an operating electric heater.)
- Please contact the nearest after-sale service center when maintenance is necessary. At the time of maintenance, the maintenance personnel must strictly comply with the Operation Manual provided by the corresponding manufacturer and any nonprofessional is prohibited from servicing the air conditioner.
- The handling, installation, storage, servicing and disposal must comply with the provisions of gas-related national laws and regulations, and national wiring regulation.
- It is necessary to recover the refrigerant in the system when servicing or scrapping an air conditioner. Be aware that this refrigerant is odorless.

This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, without supervision or instruction concerning use of the appliance by a person responsible for their safety.

Children should be supervised to ensure that they do not play with the appliance. Unit operation limits: Outdoor side 61~110°F, 80%RH, indoor side 61~90°F, 80%RH.



Electrical Requirements


Warning

Electrical Shock Hazard

- Plug into a grounded 3 prong outlet.
- Do not remove the ground prong.
- Do not use an adapter.
- Do not use an extension cord.
- Failure to follow these instructions can result in death, fire, or electrical shock.



The electrical ratings for your air conditioner are listed on the model and serial number label located on the right side of the unit (when facing the front). Specific electrical requirements are listed in the chart below. Follow the requirements below for the type of plug on the power supply cord.

Wiring Requirements	Power Supply Cord
● 115 volt (103min.—127 max) ● (8K) 0-8 amps / (12K) 0-12 amps ● (8K)10-amp time-delay fuse or circuit breaker (12K) 15-amp time-delay fuse or circuit breaker ● Use on single outlet circuit only	

Recommended Ground Method

For your personal safety, this air conditioner must be grounded. This air conditioner is equipped with a 3 prong power supply cord with a grounded plug. To minimize the possibility of electrical shock, the cord must be plugged into a 3 prong outlet and grounded in accordance with all local codes and ordinances. If a 3 prong outlet is not available, it is the customer's responsibility to have a properly grounded 3 prong outlet installed by a qualified electrician.

It is the customer's responsibility:

- To contact a qualified electrician.
- To assure that the electrical installation is adequate and in conformance with the National Electrical Code, ANSI/NFPA 70-latest edition, and all local codes and ordinances.

LCDI Power Cord and Plug

This air conditioner is equipped with an LCDI (Leakage Current Detection Interrupter) power cord that is required by UL. This power supply cord contains state-of-the-art electronics that sense leakage current. If the cord is damaged and leakage occurs, power to the unit will be disconnected.


The test and reset buttons on the LCDI Plug are used to check if the plug is functioning properly.

To test the plug:


- Plug the power cord into a grounded 3 prong outlet
- Press RESET (on some units a green light will turn on).
- Press the TEST Button, the circuit should trip and cut all power to the air conditioner (on some units a green light may turn off).
- Press the RESET button. You will hear a click and the A/C is now ready for use.

NOTES:

- The RESET button must be engaged for proper use.
- The power supply cord must be replaced if it fails to trip when the TEST button is pressed or the unit fails to reset.
- Do not use the power supply cord as an ON/OFF switch. The power supply cord is designed as a protection device.
- A damaged power supply cord must be replaced with a new power supply cord.
- The power supply cord does not contain any user serviceable parts. Opening the tamper-resistant case voids all warranty and performance claims.




Packing List




Window Air Conditioner *1




Remote Control *1



Top Rail (With sponge) *1




Lock Frame *2




Filler Panels *2
(With "Left"&"Right" marked on the front face)



Sash Lock
(Two holes) *1



Window Sash Seal
(Sponge) *1



Foam Top Window
Gasket *1
(Thin sponge for back-up using)



Insulation strip
(Sponge) *2
(Only for some models)




3/8"Screws *4



1/2"Screws *3



3/4"Screws *4



Remote Control
Batteries *2

Installation & Assembly Instructions

Some assembly is required for your new air conditioner. Please read and follow these instructions carefully.

- This air conditioner is designed to be installed in a standard double-hung window with a window width between 23" and 36" (584mm-914 mm) for 8000btu. a window width between 26" and 36" (660mm-914 mm) for 12000btu.
- The air conditioner can be installed without the accordion panels to fit in a narrow window opening. See the window dimensions.
- The Lower Sash (the lower part of the window that moves up and down) must allow for 14.5" of vertical clearance when open, for 8000btu. (See Fig.1). for 16" of vertical clearance when open, for 12000btu. (See Fig.1).
- All supporting parts must be secured to firm wood, masonry, or metal.
- The electrical outlet must be within reach of the power cord.
- The air conditioner should be tilted a minimum of 3° for proper drainage of condensate and rainwater.




Fig.1

NOTE:

- Save the product packaging and installation instructions for future reference.
- Store the air conditioner in the product box when not in use for an extended period of time.

Top Rail Assembly

The top rail must be assembled prior to installing the air conditioner in the window.

Tools Needed: Phillips Head Screwdriver

Attaching the Top Rail to the Air Conditioner

- Remove the air conditioner from the box and place it on a hard and flat surface.
- Remove top rail from the top of the packaging material as shown in Fig.A.
- Align the holes in the top rail with those on the top of the unit as shown in Fig.B.
- Secure the top rail to the unit with the 3/8" screws as shown in Fig.C.



Caution

When handling the unit, be careful to avoid cuts from the sharp metal edges and aluminum fins on the front and rear coils.




Fig.A





Fig.B



Top Rail (With sponge) *1



3/8"Screws *4




Fig.C

NOTE: For safety reasons, all 4 screws must be used to attach the top rail.

How to Install

NOTE: Top Rail and Sliding Panels at each side are offset to provide the proper pitch to the rear of (5/16"). This is necessary for proper condensed water utilization and drainage. If you are not using the Side Panels for any reason, this pitch to the rear must be maintained!

- 1 Place the unit on floor, a bench or a table. There is a Left and Right Window Filler Panel. Be sure to use the proper panel for each side. When installed the flange for securing the panel in place to the window sill should be facing into the room.
- Hold the Accordion Panel in one hand and gently pull back the center to free the open end. See Fig.2.
 - Slide the free end of the panel into the cabinet as shown in Fig.3. Slide the panel down. Be sure to leave enough space to slip the top and bottom of the frame into the rails of the cabinet.




Fig.2




Fig.3

- Once the panel has been installed on the side of the cabinet, make sure it sits securely inside the frame channel by making slight adjustments. Slide the top and bottom ends of the frame into the top and bottom rails of the cabinet. See Fig.4.
- Slide the panel all the way in and repeat on the other side.




Fig.4

- 2 Keeping a firm grip on the air conditioner, carefully place the unit into the window opening so the bottom of the air conditioner frame is against the window sill (Fig.5). Carefully close the window behind the top rail of the unit. (Remember to keep a downward tilt towards the back, to let condensate and accumulated rain water to drain out, from back side of the unit's bottom.)
- 3 Extend the side panels out against the window frame (Fig.6).




Fig.5




Fig.6

- 4 Place the frame lock between the frame extensions and the window sill as shown (Fig.7). Drive 3/4" (19 mm) locking screws through the frame lock and into the sill (Fig.8).

NOTE: To prevent window sill from splitting, drill 1/8" (3 mm) pilot holes before driving screws.




Fig.7




Fig.8

-
- 5 Drive 1/2" (12.7mm) locking screws through frame holes into window sash (Fig.9 Fig10)




Fig.9




Fig.10

- 6 To secure lower sash in place, attach right angle sash lock with 3/4" (19 mm) screws as shown (Fig.11).




Fig.11

- 7 Cut foam seal and insert in the space between the upper and lower sashes (Fig.12).




Fig.12

If AC is Blocked by Storm Window

Add wood as shown in Fig.13, or remove storm window before air conditioner is installed.




Fig.13

If Storm Window Frame must remain, be sure the drain holes or slots are not caulked or painted shut. Accumulated Rain water or Condensation water must be allowed to drain out.

Removing AC From Window

- Turn AC off and disconnect power cord.
- Remove sash seal from between windows and unscrew safety lock.
- Remove screws installed through frame and frame lock.
- Close (slide) side panels into frame.
- Keeping a firm grip on the air conditioner, raise sash and carefully "rock" air conditioner backward to drain any condensate water in base of unit. Be careful not to spill any remaining water while lifting the unit from the window. Store parts with air conditioner.

Air Conditioner Use

Operating your air conditioner properly helps you to obtain the best possible results. This section explains proper air conditioner operation.

IMPORTANT:

- If you turn off the air conditioner, wait at least 3 minutes before turning it back on. This prevents the air conditioner from blowing a fuse or tripping a circuit breaker.
- Do not try to operate your air conditioner in the cooling mode when the outside temperature is below 65°F (18°C). The inside evaporator coil will freeze up, and the air conditioner will not operate properly.

NOTE: In the event of a power failure, your air conditioner will operate at the previous settings when the power is restored.

R32 Refrigerant Safety Precautions

- Before installing the appliance, you must read the manual carefully for safety information and notes.
- A leak test must be done after the installation is completed or after servicing.
- A safety inspection must be carried out before maintaining or repairing an air conditioner using a combustible refrigerant to ensure that the fire risk is reduced to minimum.
- It is necessary to operate the machine under a controlled procedure in order to ensure that any risk arising from the combustible gas or vapor during the operation is reduced to minimum.
- Observe the requirements for the total weight of refrigerant charge and the minimum area of the room (40 sq. ft) to be equipped with the air conditioner.



1. Site Safety



Open Flames Prohibited



Minimum area observed



Ventilation Necessary

2. Operation Safety



Mind Static Electricity



Must Wear Protective Clothing
and anti-static gloves



Don't use mobile phone

3. Installation Safety



- 1) Refrigerant Leak Detector (shown) recommended.
- 2) Check for Appropriate Installation Location.

Please note that:

- The installation site should be in a well-ventilated condition.
- The sites for installing and maintaining an air conditioner using Refrigerant R32 should be free from open fire or welding, smoking, drying ovens or any other heat source which could easily produce open fire.
- It is necessary to choose the site convenient for installation or maintenance wherein the air inlets and outlets of the indoor and outdoor units are not surrounded by obstacles or close to any heat source or combustible and/or explosive environments.
- If the indoor unit suffers a refrigerant leak during the installation, all the personnel should evacuate the premises until the refrigerant leaks completely for 15 minutes. If the product is damaged, it is a must to carry such damaged product back to the maintenance station and it is prohibited to weld the refrigerant pipe or conduct other operations on the user's site.
- It is recommended to avoid installing where there are other electrical products, power switch plugs and sockets, kitchen cabinet, beds, sofas and other valuables right under the indoor side of the unit to minimize damage from accidental water leaks if the outside drainage gets blocked, and also to prevent mechanical damage from occurring.

Using Your Air Conditioner


Normal Operating Sounds

- You may hear a pinging noise caused by water hitting the condenser on rainy days, or when the humidity is high. This design feature helps remove moisture and improve efficiency.
- You may hear the thermostat click when the compressor cycles on and off.
- Water will collect in the base pan during rain or days of high humidity. The water may overflow and drip from the outside part of the unit.
- The fan may run even when the compressor is not on.

Electronic Control Panel

NOTE: This display always shows the Set temperature except when the Timer is set.

NOTE: * means only available for WIFI modes, For more information, please see the WIFI manual.



1. Digital Display:

If the timer is not set, and the operation mode is in Cool, Dry or Auto, the set (desired) temperature will be displayed. If the timer is set, the time remaining for the automatic ON or OFF will be displayed.

2. and Button:

Use these buttons on the control panel and remote to increase or decrease the Set Temperature or hours and minutes on the Timer.

Temperature range: 61°F~88°F or 16°C~31°C.

3. Power Button:

Turns the air conditioner on and off.

4. Mode Button:

Press the mode button to cycle through the various modes: Cool, Dry, Fan and Auto.

Cool Mode: The cooling function allows the air conditioner to cool the room and at the same time reduces humidity. Press the MODE button to activate the cooling function. To optimize this function adjust the temperature by pressing the up and down arrows and the speed by pressing the Fan Speed button.

Dry Mode: This function reduces the humidity of the air to make the room more comfortable. Press the MODE button to set the DRY mode. An automatic function of alternating cooling cycles and air fan is activated.

Fan Mode: Press the MODE button to set the FAN mode. Press the FAN SPEED button to adjust the speed changes in the following sequence: HIGH, MED, LOW. The unit stores the speed that was set in the previous mode of operation.

Auto Mode: In AUTO mode the unit automatically chooses the mode of operation (COOL, or FAN). In this mode the set temperature is selected automatically according to the room temperature (sensed by the temperature sensor which is incorporated in the indoor unit).

5. Timer Button:

Use this button on the control panel and remote to set the Timer.

Timer Off : The timed stop is programmed by pressing the TIMER button when the unit is ON. Set the time by pressing the button  or  until the remaining time displayed is what you want, and then press the TIMER button again to confirm the setting. The display will show the remaining ON time.

Timer On: When the unit is off, press the TIMER button for the first time, and set the temperature by pressing the button  or . Press the TIMER button a second time, set the remaining time by pressing the button  or . Press the TIMER button a third time, to confirm the setting. The display will show the remaining OFF time.

Note: The unit can be set to automatically turn off or on in 0.5-24 hours. Each press of the   buttons will increase or decrease the timer. The Timer can be set in 0.5 hour increments below 10 hours and 1 hour increments for 10 hours or above. The SET light will turn on while setting. To cancel the TIMER, press the TIMER button again.

6. Eco Button:

When the unit is in ECO mode, the ECO light will turn on. In ECO mode, the unit's fan will turn off once the room is cooled to the user-set temperature.

The unit will turn back on when the room temperature rises above the user-set temperature. Before the compressor starts, the fan motor will run for a while, then it will stop for a while, and will repeat to provide a comfortable feeling while saving energy.

7. Sleep Button:

Pressing the SLEEP button, will cause all of the display lights to turn off and the Sleep light to turn on. In SLEEP mode, the air conditioner will automatically adjust the temperature and fan speed to make the room comfortable while saving energy during the night. The set temperature will automatically increase or decrease based on the room temperature and the duration of sleep.

8. Fan Speed Button:


Press the FAN SPEED button to choose the fan speed options. You can choose HIGH, MED, LOW or auto speed in COOL mode and choose HIGH, MED, LOW in FAN mode. AUTO fan speed will adjust the speed of the fan depending on the difference between the room temperature and the set (desired) temperature.

9. Filter Button:


When the Filter Check light is off, it is not necessary to press the Filter Check button. When the Filter Check light is on, you can turn off the light by pressing the Filter Check button. After the fan motor works for 500 total hours, the Filter Check light will turn on to remind the user to clean the filter.

10. Directional Louvers:

To direct the airflow, turn the adjustment wheel to control the horizontal direction, or push it up or down to control the vertical direction of the airflow.



REMOTE CONTROL



1. POWER

Turns the air conditioner on and off.

2. Cool

Press the COOL button for COOL mode.

3. and

Use these buttons on the control panel and remote to increase or decrease the Set Temperature or hours and minutes on the Timer.

Temperature range: 61°F ~88°F or 16°C ~31°C .

4. Sleep

Pressing the SLEEP button, will cause all of the display lights to turn off and the Sleep light to turn on. In SLEEP mode, the air conditioner will automatically adjust the temperature and fan speed to make the room comfortable while saving energy during the night. The set temperature will automatically increase or decrease based on the room temperature and the duration of sleep.

5. Timer

Use buttons to set the Timer.

Timer Off : The timed stop is programmed by pressing the TIMER button when the unit is ON. Set the time by pressing the button  or  until the remaining time displayed is what you want, and then press the TIMER button again to confirm the setting. The display will show the remaining ON time.

Timer On: When the unit is off, press the TIMER button for the first time, and set the temperature by pressing the button  or . Press the TIMER button a second time, set the remaining time by pressing the button  or . Press the TIMER button a third time, to confirm the setting, The display will show the remaining OFF time.

Note: The unit can be set to automatically turn off or on in 0.5-24 hours. Each press of the   buttons will increase or decrease the timer. The Timer can be set in 0.5 hour, increments below 10 hours and 1 hour increments for 10 hours or above. The SET light will turn on while setting. To cancel the TIMER, press the TIMER button again.

6. Auto Mode

In AUTO mode the unit automatically chooses the mode of operation (COOL, or FAN).

In this mode the set temperature is selected automatically according to the room temperature (sensed by the temperature sensor which is incorporated in the indoor unit.).

7. Fan Speed

Press the FAN SPEED button to choose the fan speed options. You can choose HIGH, MED, LOW or AUTO speed in COOL mode and choose HIGH, MED, LOW in FAN mode. AUTO fan speed will adjust the speed of the fan depending on the difference between the room temperature and the set (desired) temperature.

8. Display

By pressing the DISPLAY button, you can switch off/on all lights and the LED display.

9. ECO

When the unit is in ECO mode, the ECO light will turn on. In ECO mode, the unit's fan will turn off once the room is cooled to the user set temperature. The unit will turn back on when the room temperature rises above the user set temperature. Before the compressor starts, the fan motor will run for a while, then it will stop for a while, and will repeat to provide a comfortable feeling while saving energy.

10. Fan Only

Press this button for FAN ONLY mode. In this mode the unit just ventilates the room without cooling. By pressing the FAN SPEED button, the speed changes in the following sequence: HIGH, MED, LOW and AUTO. The unit stores the speed that was set in the previous mode of operation.

Battery Size: **AAA**

NOTE: Do not mix old and new batteries or different types of AAA batteries.

Care and Cleaning


Clean your air conditioner to keep it looking new and to minimize dust build up.

Air Filter Cleaning

The air filter should be checked at least once every month to see if it needs cleaning. Trapped particles and dust can build up in the filter and may decrease airflow as well as cause the cooling coils to accumulate frost.

To clean the air filter:

- Take off the power plug, and remove the filter by sliding it out from the front right side of the air conditioner. (See Fig.14)
- Wash the filter using liquid dish soap and warm water. Rinse the filter thoroughly. Gently shake the filter to remove excess water.
- Let the filter dry completely before placing it into the air conditioner.
- If you do not wish to wash the filter, you may vacuum the filter to remove the dust and other particles.



Indents

Fig.14

Wear and Tear

To minimize wear and tear on the air conditioner, always wait at least 3 minutes before changing modes. This will help prevent the compressor from overheating and the circuit breaker from tripping.

Cabinet Cleaning

To clean the air conditioner cabinet:

- Unplug the air conditioner to prevent shock or a fire hazard. The cabinet and front panel of the air conditioner may be dusted with an oil free cloth or washed with a cloth dampened in a solution of warm water and mild liquid soap. Rinse thoroughly with a damp cloth and wipe dry.
- Never use harsh cleaners, wax or polish on the cabinet front.
- Be sure to wring excess water from the cloth before wiping around the controls. Excess water in or around the controls may cause damage to the air conditioner.

Winter Storage

To store the air conditioner when it is not in use for an extended period of time, remove it carefully from the window according to the installation instructions and cover it with plastic or place it in the original box.

Troubleshooting

Problem	Possible Causes	Solutions
The Air Conditioner will not start	The air conditioner is unplugged	Make sure the air conditioner plug is pushed completely into the outlet.
	The fuse is blown/circuit breaker is tripped	Check the house fuse/circuit breaker box and replace the fuse or reset the breaker.
	Power failure	• The unit will automatically re-start when power is restored. • There is a protective time delay (approx.3 minutes) to prevent tripping of the compressor overload. For this reason, the unit may not start normal cooling for 3 minutes after it is turned back on.
	The current interrupter device is tripped	• Press the RESET button located on the power cord plug. • If the RESET button will not stay engaged, discontinue use of the air conditioner and contact a qualified service technician.
The Air Conditioner does not cool as it should	Airflow is restricted	Make sure there are no curtains, blinds, or furniture blocking the front of the air conditioner.
	The temperature control may not be set correctly	Lower the set thermostat temperature.
	The air filter is dirty	Clean the filter. See the Cleaning and Care Section of the manual.

Problem	Possible Causes	Solutions
The Air Conditioner does not cool as it should	The room may be too warm	Please allow time for the room to cool down after turning on the air conditioner.
	Cold air is escaping	Check for open furnace registers and cold air returns.
	The cooling coils are frozen	See "Air Conditioner Freezing Up" below.
The Air Conditioner is freezing up	Ice blocks the air flow and stops the air conditioner from cooling the room	Set the MODE to Fan Only and the fan speed to HIGH.
The Remote Control is not working	• The batteries are inserted incorrectly • The batteries may be dead	• Check the position of the batteries. • Replace the batteries.
Water is dripping outside	Hot and humid weather	This is normal.
Water is dripping inside the room	The air conditioner is not correctly tilted outside	For proper water drainage, make sure the air conditioner is slightly tilted downward from the front of the unit to the rear.
Water collects in the base pan	Moisture removed from the air is draining into the base pan	This is normal for a short period in areas with low humidity and normal for a longer period in areas with high humidity.